


The Lakes (2012) Ltd
The Lakes - Stage 3E
Geotechnical Completion Report
24 June 2016



Experience
comes to life
when it is
powered by
expertise

This page has been left intentionally blank

The Lakes - Stage 3E

Prepared for
The Lakes (2012) Ltd
C/- Harrison Grierson Consultants Ltd
Level 1 Harrison Grierson House
141 Cameron Road
Tauranga

Prepared by
Coffey Geotechnics (NZ) Ltd
96 Cameron Road, Tauranga
Tauranga Central 3110 New Zealand
t: +64 7 577 4286

24 June 2016

Document authorisation

Our ref: GENZTAUC13086AP-AI

For and on behalf of Coffey



David Cullen
Engineering Geologist

Quality information

Revision history

Revision	Description	Date	Author	Reviewer	Signatory
Draft	Draft for review	21/06/2016	D Cullen	D Sullivan	D Cullen
Final	Final for issue	24/06/2016	D Cullen	D Sullivan	D Cullen

Distribution

Report Status	No. of copies	Format	Distributed to	Date
Final	1	Hardcopy + PDF	The Lakes (2012) Ltd	24/06/2016
Final	1	PDF	Harrison Grierson Consultants Ltd	24/06/2016
Final	2	Hardcopy + PDF	Tauranga City Council	24/06/2016

Table of contents

1. INTRODUCTION AND SCOPE.....	1
2. DESCRIPTION OF SUBDIVISION.....	1
3. RELATED REPORTS.....	1
3.1. Geotechnical Assessments.....	2
3.2. Contaminated Soils Report	2
3.3. Earthworks Completion Report	2
4. INVESTIGATIONS COMPLETED.....	3
5. OVERVIEW OF GEOLOGICAL CONDITIONS.....	3
6. EARTHWORKS OPERATIONS	3
6.1. Plant	3
6.2. Construction Programme	3
7. QUALITY CONTROL.....	4
7.1 Fill Control	4
8. ENGINEERING EVALUATION AND RECOMMENDATIONS	4
8.1 Fill Quality.....	4
8.2 Static Settlement	4
8.3 Slope Stability.....	4
8.4 Foundation Design & Bearing Capacity	4
8.5 Stormwater Management.....	5
9. CONCLUSION.....	5
10. LIMITATIONS	6

Important information about your Coffey Report

Appendices

Appendix A - Figures

Appendix B - Geotechnical Suitability Statement & Geotechnical Data Summary Table

Appendix C - Pre Development Investigation Data

Appendix D - Post Development Investigation Data

1. INTRODUCTION AND SCOPE

This Geotechnical Completion Report (GCR) has been prepared by Coffey Geotechnics (NZ) Ltd (Coffey) for the Lakes (2012) Limited following completion of earthworks for Stage 3E of the Lakes Subdivision and in general accordance with the conditions of Council resource consent number RC21332.

This GCR contains the results of site investigations together with as-built plans derived from Harrison Grierson Consultants Ltd (HGCL) topographical data. It describes bulk earthworks completed during the 2007-2008, 2013-2014 and 2014-2015 earthworks seasons.

The extent of earthworks observed by Coffey is shown on the appended plans (Figures 1 to 6, Appendix A). A Statement of Professional Opinion (Form G2) and Summary of Technical Data (Form G3) for the works described herein are also appended.

2. DESCRIPTION OF SUBDIVISION

Stage 3E of the Lakes subdivision is located near the southern end of Lakes Boulevard in Pyes Pa, Tauranga. The site location and original ground contours are shown on Figure 1.

Before work began, the majority of the site consisted of flat or gently rolling north-south oriented plateau at approximately RL 60m (Moturiki Datum, 1953).

During the 2007 to 2008 earthworks season, excavation of the elevated plateau was undertaken in the southern extent of Stage 3E and also within lots 352 to 355 to the west. Contours of the works completed are shown on Figure 2. The finished ground surface (surveyed in 2012) is shown on Figure 3.

In 2012 ownership of the Lakes subdivision passed from Grasshopper Farms Ltd to The Lakes (2012) Ltd. Further earthworks were completed for which additional excavation was undertaken on the plateau in the northern and eastern regions of Stage 3E. Combined cut/fill contours for the 2013-2014 and 2014-2015 earthworks are shown on Figure 4 Appendix A.

Civil infrastructure for these stages of the subdivision was installed in 2015 and 2016. The finished (March 2016) ground surface is shown on Figure 5 at approximately RL 58m in the southern/ eastern region of Stage 3E and increasing gently to approximately RL 60m in the northern/western region.

3. RELATED REPORTS

The following documents were prepared prior to or during the design and development of Stages 3E:

1. *'Pyes Pa West Urbanisation Development, Tauranga – Geotechnical Assessment Report'*, report prepared by S&L Consultants Ltd (Ref: 16944, dated October 2003).
2. *'Detailed Site Investigation for the Lakes Subdivision Stage 3, Takitimu Drive, Tauranga'*, report prepared by Coffey Environments (Ref: ENNZAU51132AA, dated 21 March 2013).
3. *'Geotechnical Investigation Report for the Lakes Subdivision – Stage 3 (Phase 1) at Pyes Pa, Tauranga'*, report prepared by Coffey (Ref: GENZTAUC13086AF-AA, dated 29 April 2013).

4. *'Summary of Works Report, The Lakes, Stage 3, Tauranga'* report prepared by Coffey Environments (Ref: ENNZAUUCK51132AB, dated 7 April 2014).
5. *'Geotechnical Investigation Report for the Lakes Subdivision – Stage 3 Zone 2 at Pyes Pa, Tauranga'*, report prepared by Coffey (Ref: GENZTAUC13086AK-AC, dated 7 April 2014).
6. *'The Lakes Subdivision Stage 3 Zone 1 Earthworks Completion Report'*, report prepared by Coffey (Ref: GENZTAUC13086AF-AE, dated 15 August 2014).

Key conclusions of the main documents are summarised below.

3.1. Geotechnical Assessments

The original geotechnical assessment for the Lakes subdivision was completed by S&L Consultants Ltd and contained an overview of geotechnical conditions for the entire Lakes project. The report concluded that the site was generally adequate for subdivision and residential development, subject to appropriate design and construction.

Subsequent geotechnical investigation reports by Coffey in April 2013 and April 2014 summarised additional investigations that were completed to specifically assess the Stage 3 area. These investigations generally confirmed the S&L conclusion that the site was adequate for subdivision.

3.2. Contaminated Soils Report

Due to the presence of farm buildings and facilities on the original site, Coffey was also engaged to conduct an environmental assessment of the proposed development area. The results of this assessment were described in the Coffey Environments report of March 2013 (Section 4, reference 2). This report identified isolated areas of possibly contaminated soil at the sites of a (suspected) pre-existing sheep dip, an above-ground fuel storage tank and a diary effluent pond.

Further investigation at the suspected sheep dip site did not find evidence of significant soil contamination in this area. Soils beneath the fuel storage tank and the effluent pond were sub-excavated during the early stage of earthworks in 2013 and were buried beneath road areas within the development area as required by the Environmental Management Plan. This work was observed and results presented by Coffey Environments in the Summary of Works Report of April 2014 (Section 4, reference 4).

3.3. Earthworks Completion Report

The August 2014 Earthworks Completion Report (ECR) concluded that the bulk earthworks undertaken in 2007-2008 and 2013-2014 were generally completed in accordance with the relevant standards and guidelines including NZS 4431 (Code of Practice for Earth Fill for Residential Development) and the Tauranga City Council Infrastructure Development Code (TCC IDC).

The ECR also referred to the presence of subsurface erosion features ('tomos') found in other Stages of the Lakes Subdivision, indicating soils below the plateau may be subject to erosion and scouring. While 'tomos' have not been observed within Stage 3E, it is possible erosional features may be encountered during construction on these lots.

4. INVESTIGATIONS COMPLETED

Geotechnical investigations have been undertaken on this and adjacent sites during each stage of the Lakes subdivision's design and construction, including five test pits that were excavated in 2012 within or near Stage 3E to depths of up to 6m to assess shallow ground conditions before the 2013-2014 work season (Coffey, TP04 –TP08 on Figure 3). Logs are included in Appendix C.

On completion of the bulk earthworks in 2016, Coffey drilled a total of 38 hand-auger boreholes to a target depth of 2m on approximately every second lot to confirm finished subgrade conditions. The location of each borehole is shown on Figure 5. Although not shown on the plan, the boreholes are numbered according to the relevant lot number. For example, the hand auger borehole on Lot 352 in Stage 3E is referred to as HAL352. Where two hand auger boreholes occur on the same lot, they are appended with the letter A and B. Logs of these boreholes are included in Appendix D.

5. OVERVIEW OF GEOLOGICAL CONDITIONS

The subject area is located on an elevated, gently sloping plateau. Below the topsoil layer, the pre-development soil profile across this plateau comprised of volcanic ashes including the Hamilton Ash and Rotoehu Ash. This ash sequence is common throughout the Tauranga area. At this location the volcanic ashes overlie ancient alluvial deposits of the Matua Sub-Group and weakly cemented pumice sands of the Te Ranga Ignimbrite.

Excavations in 2007-2008 and 2013-2014 reduced the thickness of the volcanic ashes across most of the plateau by up to 7m. The subsoils below many of the finished lots therefore comprise volcanic ash silts but in some areas excavations have penetrated through the ash layers and the finished lots are underlain by variable Matua Sub-Group soils. These include silts, sands and clays which can be highly sensitive to reworking.

6. EARTHWORKS OPERATIONS

6.1. Plant

Earthworks during the 2007-2008 season were completed by Bob Hicks Earthmovers Ltd. The contractor for the 2013-2014 and 2014-2015 seasons was JMC Civil Construction Ltd.

The main items of plant used during each of the bulk earthworks phase comprised Terex motor-scrappers and bulldozer or tractor towed 'scoops', hydraulic excavators, bulldozers, articulated all-terrain dump trucks (ADT's) and sheep's-foot rollers.

6.2. Construction Programme

Earthworks in 2007 and 2008 summer included excavations of up to 4m depth on the main plateau as shown on Figure 2.

In 2010, work on the Lakes subdivision site ceased under the original developer, Grasshopper Farms Ltd, when that company went into receivership. Records from this time are incomplete until work started again on site under The Lakes (2012) Ltd in 2012.

During the 2013-2014 and 2014-2015 earthworks seasons, the remaining earthworks were completed to form the current ground surface, including excavation of up to 6m depth within Stage 3E. Cut contours for this period are shown on Figure 4 and the finished ground surface is shown on Figure 5.

We note the cut/fill contours are shown at 1m vertical intervals. As such, fill depths of less than 1m will not appear on this plan. It is understood minor filling was completed to 'fine-tune' the finished landform and fill materials were observed in the post-development boreholes on Lots 390, 392 and 404. Fill depths shown in the *G3 – Summary of Geotechnical Data For Individual Lots* table, allow for minor earthworks shown in these areas.

Several pre-existing farm buildings and facilities were removed from site at this time. This included the sub-excavation and disposal of contaminated soils from areas around the buildings in accordance with the 2014 Summary of Works Report.

7. QUALITY CONTROL

7.1 Fill Control

As this area is within bulk cut with finish earthworks, there has not been laboratory fill testing conducted in Stage 3E. The minor fill materials observed onsite have been assessed using undrained shear strength measurements in the post-development hand auger boreholes.

8. ENGINEERING EVALUATION AND RECOMMENDATIONS

8.1 Fill Quality

Based on hand auger investigations, results indicate that the minor fill observed on parts of the site has been compacted to adequate standard (greater than 150kPa).

8.2 Static Settlement

As the entire site is now between 1m and 6m below original ground level, static settlement is not considered to be of concern within Stage 3E of the Lakes Subdivision.

8.3 Slope Stability

Similarly, it is considered that Stage 3E is not situated in proximity to a slope that may have an adverse effect on the site.

8.4 Foundation Design & Bearing Capacity

Most of the lots discussed in this GCR are underlain by natural volcanic soils which have been exposed by excavation. While the large majority of tests and investigations in these soils indicate they are adequate for standard shallow foundations, areas of relatively weak or sensitive materials have also been encountered in the post-development hand-auger boreholes.

It is therefore recommended that dwellings on the new lots be supported on pod-raft type foundations (e.g. 'rib-raft') which have been specifically designed for a geotechnical ultimate bearing capacity of 200kPa. The ground conditions under many of these lots should also be adequate for standard foundations designed in accordance with NZS 3604, however this would need to be confirmed by specific site investigation at the building consent stage.

It should be understood that due to the volcanic nature of the natural soils on this site, it is possible that local soil conditions may vary from those discussed above. Some soils observed onsite are also potentially prone to sub-surface erosion (e.g. 'tomos'). It is therefore important that any potentially soft or unsuitable soils encountered in the foundation excavations are brought to the attention of a geotechnical professional.

8.5 Stormwater Management

To further reduce the potential for surface and sub-surface erosion, all stormwater from impervious areas within the development will need to be carefully collected and piped to a safe disposal point or to the reticulated network. Particular care should be taken to avoid areas of ponded stormwater or concentrated flows around and under buildings or structures.

9. CONCLUSION

Based on the observations and investigations presented in this report and with some reliance on the diligence of the earthworks contractors, it is concluded that the earthworks and subdivision of Stage 3E have been completed in general accordance with our previous recommendations and current Tauranga City Council Infrastructure Development Code.

10. LIMITATIONS

This report has been prepared solely for the use of the client, The Lakes (2012) Limited, their professional advisers and the relevant Territorial Authorities in relation to the specific project described herein. No liability is accepted in respect of its use for any other purpose or by any other person or entity. All future owners of this property should seek professional geotechnical advice to satisfy themselves as to its ongoing suitability for their intended use.

The opinions, recommendations and comments given in this report result from the application of normal methods of site investigation. As the post construction factual evidence has been obtained solely from boreholes and test pits, which by their nature only provide information about a relatively small volume of subsoils, there may be special conditions pertaining to this site which have not been disclosed by the investigation and which have not been taken into account in the report.

For and on behalf of Coffey

Report Prepared By:



D B CULLEN
Engineering Geologist

Report Reviewed By:





D SULLIVAN
Principal Geotechnical Engineer

Geotechnical Suitability Statement Signed By:



R TELFORD
TCC Category 2 Geotechnical Engineer

Appendix A - Figures




LEGEND

— EXTENT OF STAGE 3E

- NOTES:**
1. Contour data of original pre-earthworks landform from Harrison Grierson Consultants Ltd, May 2007.
 2. Contours shown at 1.0m intervals to Moturiki Datum.
 3. Lot layout and numbering from Harrison Grierson Consultants Ltd, March 2016.



revision	rev	description	drawn	approved	date






drawn	DBC
approved	RBT
date	09-06-2016
scale	1:2000
original size	A3




client:	The Lakes (2012) Ltd		
project:	The Lakes Stage 3E Geotechnical Completion Report		
title:	Original Site Contour Plan		
project no:	13086AP-AI	figure no:	1
rev:	-		



LEGEND	
	EXTENT OF STAGE 3E
	CUT CONTOURS
	FILL CONTOURS

- NOTES:
1. Cut/Fill contours show difference between May 2007 and May 2008 surveys. Provided by Harrison Grierson Consultants Ltd. Contours are at 1m intervals.
 2. Lot layout and numbering from Harrison Grierson Consultants Ltd, March 2016.



revision	rev	description	drawn	approved	date



drawn	DBC
approved	RBT
date	09-06-2016
scale	1:2000
original size	A3





client:	The Lakes (2012) Ltd		
project:	The Lakes Stage 3E Geotechnical Completion Report		
title:	2007-2008 Earthworks Contour Plan		
project no:	13086AP-AI	figure no:	2
rev:	-		




- NOTES:
1. Contour data of 2012 landform from Harrison Grierson Consultants Ltd.
 2. Contours shown at 1.0m intervals to Moturiki Datum.
 3. Lot layout and numbering from Harrison Grierson Consultants Ltd, March 2016.

LEGEND

-  EXTENT OF STAGE 3E
-  TEST PIT LOCATION (COFFEY 2012)



revision	rev	description	drawn	approved	date



drawn	DBC
approved	RBT
date	09-06-2016
scale	1:2000
original size	A3



client:	The Lakes (2012) Ltd		
project:	The Lakes Stage 3E Geotechnical Completion Report		
title:	2012 Contour Plan		
project no:	13086AP-AI	figure no:	3
rev:	-		




LEGEND

- EXTENT OF STAGE 3E
- CUT CONTOURS
- FILL CONTOURS

- NOTES:**
1. Cut/Fill contours show difference between 2012 and March 2016 surveys. Provided by Harrison Grierson Consultants Ltd. Contours are at 1m intervals.
 2. Lot layout and numbering from Harrison Grierson Consultants Ltd, March 2016.



revision	rev	description	drawn	approved	date



drawn	DBC
approved	RBT
date	09-06-2016
scale	1:2000
original size	A3



client:	The Lakes (2012) Ltd		
project:	The Lakes Stage 3E Geotechnical Completion Report		
title:	2013-2016 Earthworks Contour Plan		
project no:	13086AP-AI	figure no:	4
rev:	-		




NOTES:
 1. Contour data of March 2016 landform from Harrison Grierson Consultants Ltd.
 2. Contours shown at 1.0m intervals to Moturiki Datum.
 3. Lot layout and numbering from Harrison Grierson Consultants Ltd, March 2016.
 4. Hand auger boreholes are numbered according to the relevant lot number. Where two boreholes occur on the same lot, they are appended with the letter A and B.

LEGEND

- EXTENT OF STAGE 3E
- HAND AUGER BOREHOLE LOCATIONS

revision	rev	description	drawn	approved	date



drawn	DBC
approved	RBT
date	09-06-2016
scale	1:2000
original size	A3



client:	The Lakes (2012) Ltd		
project:	The Lakes Stage 3E Geotechnical Completion Report		
title:	2016 Contour Plan		
project no:	13086AP-AI	figure no:	5
rev:	-		

**Appendix B - Geotechnical Suitability Statement &
Geotechnical Data Summary Table**

**STATEMENT OF PROFESSIONAL OPINION AS TO THE
GEOTECHNICAL SUITABILITY OF LAND FOR BUILDING**

NAME OF SUBDIVISION	The Lakes Subdivision – Stage 3E
COUNCIL FILE NUMBER RC No:	RC21332
ENGINEER RESPONSIBLE FOR DEVELOPMENT	Robert Telford
QUALIFICATIONS:	TCC Category 2 Geotechnical Engineer

I, Robert Telford of Coffey Geotechnics Ltd, 96 Cameron Road, Tauranga, hereby confirm that:

- 1) I am a professional person, appropriately qualified with experience in geomechanics to ascertain the suitability of the land for building development and was retained as the Soils Engineer to the above development.
- 2) An appropriate level of site investigation and construction supervision has been carried out under my direction and is described in our development evaluation reports dated 29 April 2013 and 7 April 2014.
- 3) In my professional opinion, not to be construed as a guarantee, I consider that:
 - a) The areas shown in my report dated 24 June 2016 of each new allotment are suitable for the erection thereon of the building types appropriate to the zoning of the land, provided that reference is made to my Geotechnical Completion Report Ref. GENZTAUC13086AP-AI, dated 24 June 2016.
 - ~~b) The earth fills shown on the attached Plans ref Figure 02 & Figure 04 have been placed in general accordance with the requirements of the Infrastructure Development Code.~~
 - c) The completed works give due regard to all land slope and foundation stability considerations.
 - ~~d) The filled ground is suitable for the erection thereon of residential buildings requiring specific design subject to the recommendations presented in my Geotechnical Completion Report Ref. GENZTAUC13086AP-AI, dated 24 June 2016.~~
 - e) The original ground not affected by filling is suitable for the erection thereon of residential buildings requiring specific design subject to the recommendations presented in my Geotechnical Completion Report Ref. GENZTAUC13086AP-AI, dated 24 June 2016.
- 4) This professional opinion is furnished to the Council and the owner for their purposes alone, on the express condition that it will not be relied upon by any other person and does not remove the necessity for the normal inspection of foundation conditions at the time of erection for any dwelling.

Signed



Date: 24 June 2016



PRODUCER STATEMENT
SUITABILITY OF LAND FOR BUILDING DEVELOPMENT

INFRASTRUCTURE DEVELOPMENT CODE

G2

VERSION 1
July 2011

1

DP No:	Lot 1001 DP486181	Property Address	310 Lakes Boulevard, Pyes Pa	RC No:	21332
--------	-------------------	------------------	------------------------------	--------	-------

Lot No:	Area (m ²)	Subsurface data						Foundations		Building Restriction Line	S/W Specific Design	S/W Soakage	S/W Reticulate	Designated Building Platform	Minimum Building Platform	Compressible Soils	On-Site Effluent Disposal	Consent Notice	Comments
		Shear Strength (kPa) at 0.5m depth	Subdivision Filling		Natural Topography Unworked Y/N	Natural Topography Earthworked		Conventional Shallow Foundation to NZS 3604:2011 Y/N/NA	Specific Design Y/N/NA										
			Y/N	Depth (m)		Y/N	Depth (m)												

352	552	>183	N	-	N	Y	3	N	Y	N	N	N	Y	N	N	N	N	Y	Pod-raft type foundations specifically designed for geotechnical ultimate bearing capacity 200kPa, subject to Section 8 of Coffey GCR ref: GENZTAUC13086AP-AI. N/T = Not Tested.
353	550	N/T	N	-	N	Y	2	N	Y	N	N	N	Y	N	N	N	N	Y	
354	481	>202	N	-	N	Y	2	N	Y	N	N	N	Y	N	N	N	N	Y	
355	520	N/T	N	-	N	Y	2	N	Y	N	N	N	Y	N	N	N	N	Y	
356	560	>202	N	-	N	Y	1	N	Y	N	N	N	Y	N	N	N	N	Y	
357	480	N/T	N	-	N	Y	1	N	Y	N	N	N	Y	N	N	N	N	Y	
358	520	>183	N	-	N	Y	1	N	Y	N	N	N	Y	N	N	N	N	Y	
359	480	N/T	N	-	N	Y	1	N	Y	N	N	N	Y	N	N	N	N	Y	
360	560	180	N	-	N	Y	1	N	Y	N	N	N	Y	N	N	N	N	Y	
361	487	N/T	N	-	N	Y	1	N	Y	N	N	N	Y	N	N	N	N	Y	
362	476	183	N	-	N	Y	0	N	Y	N	N	N	Y	N	N	N	N	Y	



SUMMARY OF GOTECHNICAL DATA FOR INDIVIDUAL LOTS

INFRASTRUCTURE DEVELOPMENT CODE

G3

VERSION 1

Julv 2011

1

DP No:	Lot 1001 DP486181	Property Address	310 Lakes Boulevard, Pyes Pa	RC No:	21332
--------	-------------------	------------------	------------------------------	--------	-------

Lot No:	Area (m ²)	Subsurface data						Foundations		Building Restriction Line	S/W Specific Design	S/W Soakage	S/W Reticulate	Designated Building Platform	Minimum Building Platform	Compressible Soils	On-Site Effluent Disposal	Consent Notice	Comments
		Shear Strength (kPa) at 0.5m depth	Subdivision Filling		Natural Topography Unworked Y/N	Natural Topography Earthworked		Conventional Shallow Foundation to NZS 3604:2011 Y/N/NA	Specific Design Y/N/NA										
			Y/N	Depth (m)		Y/N	Depth (m)												

363	526	N/T	N	-	N	Y	0	N	Y	N	N	N	Y	N	N	N	N	Y	Pod-raft type foundations specifically designed for geotechnical ultimate bearing capacity 200kPa, subject to Section 8 of Coffey GCR ref: GENZTAUC13086AP-AI. N/T = Not Tested.
364	553	158	N	-	N	Y	0	N	Y	N	N	N	Y	N	N	N	N	Y	
365	537	N/T	N	-	N	Y	1	N	Y	N	N	N	Y	N	N	N	N	Y	
366	540	169	N	-	N	Y	1	N	Y	N	N	N	Y	N	N	N	N	Y	
367	580	N/T	N	-	N	Y	1	N	Y	N	N	N	Y	N	N	N	N	Y	
368	475	>183	N	-	N	Y	1	N	Y	N	N	N	Y	N	N	N	N	Y	
369	499	N/T	N	-	N	Y	1	N	Y	N	N	N	Y	N	N	N	N	Y	
370	439	>202	N	-	N	Y	1	N	Y	N	N	N	Y	N	N	N	N	Y	
371	422	N/T	N	-	N	Y	1	N	Y	N	N	N	Y	N	N	N	N	Y	
372	387	>183	N	-	N	Y	1	N	Y	N	N	N	Y	N	N	N	N	Y	



SUMMARY OF GOTECHNICAL DATA FOR INDIVIDUAL LOTS

INFRASTRUCTURE DEVELOPMENT CODE

G3

VERSION 1

July 2011

1

DP No:	Lot 1001 DP486181	Property Address	310 Lakes Boulevard, Pyes Pa	RC No:	21332
--------	-------------------	------------------	------------------------------	--------	-------

Lot No:	Area (m ²)	Subsurface data						Foundations		Building Restriction Line	S/W Specific Design	S/W Soakage	S/W Reticulate	Designated Building Platform	Minimum Building Platform	Compressible Soils	On-Site Effluent Disposal	Consent Notice	Comments
		Shear Strength (kPa) at 0.5m depth	Subdivision Filling		Natural Topography Unworked	Natural Topography Earthworked		Conventional Shallow Foundation to NZS 3604:2011	Specific Design										
			Y/N	Depth (m)		Y/N	Depth (m)												

373	388	N/T	N	-	N	Y	1	N	Y	N	N	N	Y	N	N	N	N	Y	Pod-raft type foundations specifically designed for geotechnical ultimate bearing capacity 200kPa, subject to Section 8 of Coffey GCR ref: GENZTAUC13086AP-AI. N/T = Not Tested.
374	436	173	N	-	N	Y	1	N	Y	N	N	N	Y	N	N	N	N	Y	
375	468	N/T	N	-	N	Y	1	N	Y	N	N	N	Y	N	N	N	N	Y	
376	455	>202	N	-	N	Y	1	N	Y	N	N	N	Y	N	N	N	N	Y	
377	508	N/T	N	-	N	Y	1	N	Y	N	N	N	Y	N	N	N	N	Y	
378	628	156	N	-	N	Y	2	N	Y	N	N	N	Y	N	N	N	N	Y	
379	461	N/T	N	-	N	Y	4	N	Y	N	N	N	Y	N	N	N	N	Y	
380	449	108	N	-	N	Y	6	N	Y	N	N	N	Y	N	N	N	N	Y	
381	435	N/T	N	-	N	Y	5	N	Y	N	N	N	Y	N	N	N	N	Y	
382	408	>183	N	-	N	Y	4	N	Y	N	N	N	Y	N	N	N	N	Y	



SUMMARY OF GOTECHNICAL DATA FOR INDIVIDUAL LOTS

INFRASTRUCTURE DEVELOPMENT CODE

G3

VERSION 1

July 2011

1

DP No:	Lot 1001 DP486181	Property Address	310 Lakes Boulevard, Pyes Pa	RC No:	21332
--------	-------------------	------------------	------------------------------	--------	-------

Lot No:	Area (m ²)	Subsurface data						Foundations		Building Restriction Line	S/W Specific Design	S/W Soakage	S/W Reticulate	Designated Building Platform	Minimum Building Platform	Compressible Soils	On-Site Effluent Disposal	Consent Notice	Comments
		Shear Strength (kPa) at 0.5m depth	Subdivision Filling		Natural Topography Unworked	Natural Topography Earthworked		Conventional Shallow Foundation to NZS 3604:2011	Specific Design										
			Y/N	Depth (m)		Y/N	Depth (m)												

383	555	>202	N	-	N	Y	5	N	Y	N	N	N	Y	N	N	N	N	Y	Pod-raft type foundations specifically designed for geotechnical ultimate bearing capacity 200kPa, subject to Section 8 of Coffey GCR ref: GENZTAUC13086AP-AI. N/T = Not Tested.
384	588	74	N	-	N	Y	6	N	Y	N	N	N	Y	N	N	N	N	Y	
385	400	>202	N	-	N	Y	4	N	Y	N	N	N	Y	N	N	N	N	Y	
386	445	>202	N	-	N	Y	3	N	Y	N	N	N	Y	N	N	N	N	Y	
387	434	133	N	-	N	Y	3	N	Y	N	N	N	Y	N	N	N	N	Y	
388	409	>202	N	-	N	Y	3	N	Y	N	N	N	Y	N	N	N	N	Y	
389	417	>202	Y	< 1	N	Y	3	N	Y	N	N	N	Y	N	N	N	N	Y	
390	452	>202	Y	< 1	N	Y	3	N	Y	N	N	N	Y	N	N	N	N	Y	
391	506	N/T	Y	< 1	N	Y	4	N	Y	N	N	N	Y	N	N	N	N	Y	
392	546	>202	Y	< 1	N	Y	4	N	Y	N	N	N	Y	N	N	N	N	Y	



SUMMARY OF GOTECHNICAL DATA FOR INDIVIDUAL LOTS

INFRASTRUCTURE DEVELOPMENT CODE

G3

VERSION 1

July 2011

1

DP No:	Lot 1001 DP486181	Property Address	310 Lakes Boulevard, Pyes Pa	RC No:	21332
--------	-------------------	------------------	------------------------------	--------	-------

Lot No:	Area (m ²)	Subsurface data						Foundations		Building Restriction Line	S/W Specific Design	S/W Soakage	S/W Reticulate	Designated Building Platform	Minimum Building Platform	Compressible Soils	On-Site Effluent Disposal	Consent Notice	Comments
		Shear Strength (kPa) at 0.5m depth	Subdivision Filling		Natural Topography Unworked	Natural Topography Earthworked		Conventional Shallow Foundation to NZS 3604:2011	Specific Design										
			Y/N	Depth (m)		Y/N	Depth (m)												

393	536	N/T	Y	< 1	N	Y	5	N	Y	N	N	N	Y	N	N	N	N	Y	Pod-raft type foundations specifically designed for geotechnical ultimate bearing capacity 200kPa, subject to Section 8 of Coffey GCR ref: GENZTAUC13086AP-AI. N/T = Not Tested.
394	606	>183	Y	< 1	N	Y	4	N	Y	N	N	N	Y	N	N	N	N	Y	
395	420	N/T	Y	< 1	N	Y	4	N	Y	N	N	N	Y	N	N	N	N	Y	
396	408	>183	N	-	N	Y	5	N	Y	N	N	N	Y	N	N	N	N	Y	
397	468	N/T	Y	< 1	N	Y	4	N	Y	N	N	N	Y	N	N	N	N	Y	
398	467	>183	Y	< 1	N	Y	3	N	Y	N	N	N	Y	N	N	N	N	Y	
399	461	N/T	Y	< 1	N	Y	3	N	Y	N	N	N	Y	N	N	N	N	Y	
400	459	>202	Y	< 1	N	Y	2	N	Y	N	N	N	Y	N	N	N	N	Y	
401	459	N/T	N	-	N	Y	2	N	Y	N	N	N	Y	N	N	N	N	Y	
402	455	>183	N	-	N	Y	2	N	Y	N	N	N	Y	N	N	N	N	Y	



SUMMARY OF GOTECHNICAL DATA FOR INDIVIDUAL LOTS

INFRASTRUCTURE DEVELOPMENT CODE

G3

VERSION 1

July 2011

1

DP No:	Lot 1001 DP486181	Property Address	310 Lakes Boulevard, Pyes Pa	RC No:	21332
--------	-------------------	------------------	------------------------------	--------	-------

Lot No:	Area (m ²)	Subsurface data						Foundations		Building Restriction Line	S/W Specific Design	S/W Soakage	S/W Reticulate	Designated Building Platform	Minimum Building Platform	Compressible Soils	On-Site Effluent Disposal	Consent Notice	Comments
		Shear Strength (kPa) at 0.5m depth	Subdivision Filling		Natural Topography Unworked Y/N	Natural Topography Earthworked		Conventional Shallow Foundation to NZS 3604:2011 Y/N/NA	Specific Design Y/N/NA										
			Y/N	Depth (m)		Y/N	Depth (m)												

403	458	N/T	N	-	N	Y	2	N	Y	N	N	N	Y	N	N	N	N	Y
404	416	>202	N	-	N	Y	4	N	Y	N	N	N	Y	N	N	N	N	Y
405	419	N/T	N	-	N	Y	3	N	Y	N	N	N	Y	N	N	N	N	Y
406	425	>183	N	-	N	Y	2	N	Y	N	N	N	Y	N	N	N	N	Y
407	429	N/T	N	-	N	Y	2	N	Y	N	N	N	Y	N	N	N	N	Y
408	431	>202	N	-	N	Y	2	N	Y	N	N	N	Y	N	N	N	N	Y
409	430	N/T	N	-	N	Y	1	N	Y	N	N	N	Y	N	N	N	N	Y
410	428	N/T	N	-	N	Y	1	N	Y	N	N	N	Y	N	N	N	N	Y
411	424	>202	N	-	N	Y	1	N	Y	N	N	N	Y	N	N	N	N	Y
412	472	55	N	-	N	Y	1	N	Y	N	N	N	Y	N	N	N	N	Y

Pod-raft type foundations specifically designed for geotechnical ultimate bearing capacity 200kPa, subject to Section 8 of Coffey GCR ref: GENZTAUC13086AP-AI.

N/T = Not Tested.



SUMMARY OF GOTECHNICAL DATA FOR INDIVIDUAL LOTS

INFRASTRUCTURE DEVELOPMENT CODE

G3

VERSION 1

July 2011

1

Appendix C - Pre Development Investigation Data

Trial Pit No. **TP04**
 Sheet 1 of 1
 Project No: **GENZTAUC13086AF**
 Date started: **14.3.2013**
 Date completed: **14.3.2013**
 Logged by: **RBT**
 Checked by: **RBT**

Engineering Log - Trial Pit

Client: **THE LAKES 2012 LTD**
 Principal:
 Project: **THE LAKES STAGE 3 CONSTRUCTION**
 Trial pit location: **Refer to site plan**

Equipment type: Pit Orientation: Easting: 368588.5 m R.L. Surface:
 Excavation dimensions: m long m wide Vane No: DR2244 Northing: 799726.9 m Datum:

excavation information				material substance							
stratigraphy	water	notes samples, tests, etc	depth metres	graphic log	classification symbol	material	moisture condition	consistency/density index	vane shear (remoulded/peak) kPa	structure and additional observations	
TS Younger Ash	Groundwater not encountered	Sample 1	1		OL	Organic SILT with trace clay, dark grey/brown, occasional wood fragments and building debris, friable. (FILL)	D				
		Sample 2	1		ML	SILT with minor very fine sand, light yellow/brown. Dry, friable, very stiff. - occasional tree roots (2-5mm).			UTP		
		Sample 3	2		ML	SILT with minor clay; orange/brown, occasional rootlets. Very slight plasticity, moist.	M				
			2		ML	SILT with trace to minor fine sand and trace clay; bright orange. Stiff, friable to very slightly cohesive, moist.	M-W				
			2		ML	SILT with trace sand and minor clay; orange/brown. Stiff in-situ but becomes greasy when reworked, moist to wet.	M				
RA		Sample 4	3		SP	SAND with trace to minor silt; light orange/grey. Pumiceous, friable, moist. - becomes pale orange/white and minor to some silt below 3.4m.					
HA		Sample 5	4		ML	Clayey SILT; chocolate brown, very stiff in-situ, friable when reworked. Non plastic, moist. - becoming mottled chocolate brown/orange brown. - becoming orange brown.			UTP		
			5			(max. reach of excavator) RA = Rotoehu Ash HA = Hamilton Ash Test pit TP04 terminated at 4.8 metres.					
			6								

Sketch

classification symbols and soil description based on New Zealand Geotechnical Society Inc 2005	vane shear (kPa) ● remoulded × peak >>× peak greater than 200kPa UTP unable to penetrate water 10/1/98 water level on date shown water inflow water outflow	moisture D dry M moist W wet S saturated	consistency/ density index VS very soft VL very loose S soft L loose F firm MD medium dense St stiff D dense VSt very stiff VD very dense H hard
notes, samples, tests U ₅₀ undisturbed sample 50mm diameter U ₆₃ undisturbed sample 63mm diameter D disturbed sample Bs bulk sample E environmental sample R refusal			

TRIAL PIT TEST PITS 150313.GPJ COFFEY.GDT 28.3.13

Trial Pit No. **TP05**
 Sheet 1 of 1
 Project No: **GENZTAUC13086AF**
 Date started: **14.3.2013**
 Date completed: **14.3.2013**
 Logged by: **KB**
 Checked by: **RBT**

Engineering Log - Trial Pit

Client: **THE LAKES 2012 LTD**
 Principal:
 Project: **THE LAKES STAGE 3 CONSTRUCTION**
 Trial pit location: **Refer to site plan**

Equipment type: Pit Orientation: Easting: 368587.6 m R.L. Surface:
 Excavation dimensions: m long m wide Vane No: DR2244 Northing: 799812.3 m Datum:

excavation information				material substance							
stratigraphy	water	notes samples, tests, etc	RL	depth metres	graphic log	classification symbol	material	moisture condition	consistency/density index	vane shear (remoulded) (peak) kPa	structure and additional observations
Younger Ash	Groundwater not encountered	Sample 11		0		OL	TOPSOIL.	D			
		Sample 12		1		ML	SILT; light brown. Friable, dry.	M			
		Sample 13		2		ML	SILT with trace sand and clay; orange brown. Low plasticity and greasy when reworked.				
				3		ML	SILT with trace to minor sand and trace clay; bright orange. - becoming orange brown.				
				4		SP	Fine to coarse SAND with trace silt; orange brown. Well graded. - becoming light brown/white with occasional silt lenses.				
				5		ML	Clayey SILT; brown. Low plasticity and greasy when reworked. - becoming orange brown mottled brown, less stiff. - becoming light brown/orange brown.				
Hamilton Ash		Sample 14		4		ML	Clayey SILT; brown. Low plasticity and greasy when reworked.			UTP	
		Sample 15		5							
		Sample 16		6							
							(Target depth) RA = Rotoehu Ash				

Sketch Test pit TP05 terminated at 6 metres.

classification symbols and soil description based on New Zealand Geotechnical Society Inc 2005	vane shear (kPa) ● remoulded × peak >>× peak greater than 200kPa UTP unable to penetrate water 10/1/98 water level on date shown water inflow water outflow	moisture D dry M moist W wet S saturated	consistency/ density index VS very soft VL very loose S soft L loose F firm MD medium dense St stiff D dense VSt very stiff VD very dense H hard
notes, samples, tests U ₅₀ undisturbed sample 50mm diameter U ₆₃ undisturbed sample 63mm diameter D disturbed sample Bs bulk sample E environmental sample R refusal			

TRIAL PIT TEST PITS 150813.GPJ COFFEY.GDT 28.3.13

Trial Pit No. **TP06**
 Sheet 1 of 1
 Project No: **GENZTAUC13086AF**
 Date started: **14.3.2013**
 Date completed: **14.3.2013**
 Logged by: **KB**
 Checked by: **RBT**

Engineering Log - Trial Pit

Client: **THE LAKES 2012 LTD**
 Principal:
 Project: **THE LAKES STAGE 3 CONSTRUCTION**
 Trial pit location: **Refer to site plan**

Equipment type: Pit Orientation: Easting: 368704.4 m R.L. Surface:
 Excavation dimensions: m long m wide Vane No: DR2244 Northing: 799943.7 m Datum:

excavation information				material substance							
stratigraphy	water	notes samples, tests, etc	RL	depth metres	graphic log	classification symbol	material	moisture condition	consistency/density index	vane shear (remoulded) (kPa)	structure and additional observations
Younger Ash	Groundwater not encountered	Sample 17		1		OL	TOPSOIL	D			
		Sample 18		1		ML	SILT; light brown, friable and dry.				
		Sample 19		2		ML	- becoming orange brown and moist.	M			
		Sample 19		2		ML	SILT with trace fine sand and clay; orange brown. Greasy when reworked.				
		Sample 19		2		ML	SILT with minor sand and trace clay.; bright orange. Low plasticity.				
RA	Groundwater not encountered	Sample 20		3		SP	Fine to coarse SAND with trace silt; orange brown, occasional silty lenses. Well graded.				
		Sample 20		3		SP	- becoming white/light brown.				
Hamilton Ash	Groundwater not encountered	Sample 21		4		ML	Clayey SILT; brown. Medium plasticity, very stiff, greasy when reworked.				UTP
		Sample 21		4		ML	- becoming orange brown and less stiff.				
				5							
				6			(Target depth) RA = Rotoehu Ash Test pit TP06 terminated at 5 metres.				

Sketch

classification symbols and soil description based on New Zealand Geotechnical Society Inc 2005	vane shear (kPa) ● remoulded × peak >>× peak greater than 200kPa UTP unable to penetrate water 10/1/98 water level on date shown water inflow water outflow	moisture D dry M moist W wet S saturated	consistency/ density index VS very soft VL very loose S soft L loose F firm MD medium dense St stiff D dense VSt very stiff VD very dense H hard
notes, samples, tests U ₅₀ undisturbed sample 50mm diameter U ₆₃ undisturbed sample 63mm diameter D disturbed sample Bs bulk sample E environmental sample R refusal			

TRIAL PIT TEST PITS 150313.GPJ COFFEY.GDT 28.3.13

Trial Pit No. **TP07**
 Sheet 1 of 1
 Project No: **GENZTAUC13086AF**
 Date started: **14.3.2013**
 Date completed: **14.3.2013**
 Logged by: **KB**
 Checked by: **RBT**

Engineering Log - Trial Pit

Client: **THE LAKES 2012 LTD**
 Principal:
 Project: **THE LAKES STAGE 3 CONSTRUCTION**
 Trial pit location: **Refer to site plan**

Equipment type: Pit Orientation: Easting: 368767.5 m R.L. Surface:
 Excavation dimensions: m long m wide Vane No: DR2244 Northing: 799923.9 m Datum:

excavation information				material substance							
stratigraphy	water	notes samples, tests, etc	RL	depth metres	graphic log	classification symbol	material	moisture condition	consistency/density index	vane shear (remoulded) (peak) kPa	structure and additional observations
Younger Ash	Groundwater not encountered	Sample 22		0		OL	TOPSOIL	D			
		Sample 23		1		ML	SILT; light brown. Friable and dry.	M			
		Sample 24		2		ML	SILT with trace sand and clay; orange brown. Greasy when reworked.				
				2		ML	SILT with minor sand; bright orange.				
		Sample 25		3		SP	SAND with trace silt; orange brown, fine to coarse grained, pumiceous. Well graded.				
				3			- becoming light brown/white.				
HA	Groundwater not encountered	Sample 26		4		ML	Clayey SILT; brown. Medium plasticity and greasy when reworked.				
				5			- becoming orange brown.				
				6			(Target depth) RA = Rotoehu Ash HA = Hamilton Ash Test pit TP07 terminated at 5 metres.				

Sketch

classification symbols and soil description based on New Zealand Geotechnical Society Inc 2005	vane shear (kPa) ● remoulded × peak >>× peak greater than 200kPa UTP unable to penetrate water 10/1/98 water level on date shown water inflow water outflow	moisture D dry M moist W wet S saturated	consistency/ density index VS very soft VL very loose S soft L loose F firm MD medium dense St stiff D dense VSt very stiff VD very dense H hard
--	---	---	---

Trial Pit No. **TP08**
 Sheet 1 of 1
 Project No: **GENZTAUC13086AF**
 Date started: **15.3.2013**
 Date completed: **15.3.2013**
 Logged by: **RBT**
 Checked by: **RBT**

Engineering Log - Trial Pit

Client: **THE LAKES 2012 LTD**
 Principal:
 Project: **THE LAKES STAGE 3 CONSTRUCTION**
 Trial pit location: **Refer to site plan**

Equipment type: Pit Orientation: Easting: 368724 m R.L. Surface:
 Excavation dimensions: m long m wide Vane No: DR2244 Northing: 799993 m Datum:

excavation information				material substance							
stratigraphy	water	notes samples, tests, etc	RL	depth metres	graphic log	classification symbol	material	moisture condition	consistency/density index	vane shear (remoulded) (peak) kPa	structure and additional observations
Younger Ash	Groundwater not encountered	Sample 27		1		OL	Organic SILT with numerous fine rootlets; greyish brown.	D			
		Sample 28		1.5		ML	SILT with trace to minor clay, some fine rootlets; yellowish brown. Stiff, dry, friable. - becoming moist, minor clay, occasional rootlets. - becoming mottled yellow/orange brown.	M			
		Sample 29		2		SP	Fine to coarse SAND with trace silt; yellow/brown with black flecks. - trace very fine sand, moist.				
		Sample 30		3		SP	Fine to medium SAND with minor silt; pale yellow/white. Pockets rework to soft sandy silt with some clay, slightly plastic.	M-W			
		Sample 31		4		CL	Silty CLAY; chocolate brown with white flecks. Stiff to very stiff in-situ, soft and with medium to high plasticity when reworked.				
		Sample 31		4.5		ML	SILT with trace clay and trace fine sand; yellowish brown. Very stiff to hard, non plastic and moist.				
		Sample 32		5.2		ML	SILT with minor clay; orangish brown. Reworks to silty clay, moderately plastic, soft to firm.				
(Target depth) RA = Rotoehu Ash HA = Hamilton Ash Test pit TP08 terminated at 5.2 metres.											

Sketch

classification symbols and soil description based on New Zealand Geotechnical Society Inc 2005	vane shear (kPa) ● remoulded × peak >>> peak greater than 200kPa UTP unable to penetrate water 10/1/98 water level on date shown water inflow water outflow	moisture D dry M moist W wet S saturated	consistency/ density index VS very soft VL very loose S soft L loose F firm MD medium dense St stiff D dense VSt very stiff VD very dense H hard
notes, samples, tests U ₅₀ undisturbed sample 50mm diameter U ₆₃ undisturbed sample 63mm diameter D disturbed sample Bs bulk sample E environmental sample R refusal			

Appendix D - Post Development Investigation Data

Engineering Log - Hand Auger



client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 352**

Borehole ID: **HAL352**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **30 May 2016**
 date completed: **30 May 2016**
 logged by: **NM**
 checked by: **DBC**

position: E: 368485; N: 799970 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: DR2244

drilling information				material substance													
method & support	1 penetration	2 penetration	3 penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations		
HA	N	N	N	Not Encountered	VS >183 kPa	0.0	0.0			ORGANIC SILT: low plasticity, dark brown.	M	VSt to H			TOPSOIL		
					VS >183 kPa	0.0	0.1	ML	SILT: low plasticity, orange brown, with fine to medium grained sand.							MATUA SUB-GROUP	
					VS >183 kPa	0.0	0.2	SP	SAND: fine to medium grained, white, with minor silt.								
					VS >183 kPa	0.0	0.3	ML	Sandy SILT: non plastic, white, with fine grained sand.								
					VS >183 kPa	0.0	0.4	ML	SILT: low plasticity, orange brown, with minor fine grained sand, trace clay.	D to M							
					VS >183 kPa	0.0	0.5		1.0 m: soil is friable.	D							
HA	N	N	N	Not Encountered	VS UTP	0.5	0.5										
					VS UTP	0.5	1.0										
					VS UTP	0.5	1.5										
HA	N	N	N	Not Encountered	VS UTP	1.0	1.0			1.7 m: with some silt.	M						
					VS >183 kPa	1.0	2.0										
Hand Auger HAL352 terminated at 2.0 m Target depth																	

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:40

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing penetration  no resistance ranging to refusal water  10-Oct-12 water level on date shown water inflow water outflow	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	---	--	--	--

* bit shown by suffix
 e.g. AD/T
 B blank bit
 T TC bit
 V V bit

Engineering Log - Hand Auger



client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 354**

Borehole ID: **HAL354**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **30 May 2016**
 date completed: **30 May 2016**
 logged by: **ODS**
 checked by: **DBC**

position: E: 368468; N: 800003 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: SL588

drilling information				material substance											
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations		
method & support: 1 penetration 2 3 HA N Not Encountered	1 2 3	Not Encountered	VS >202 kPa		0.0 - 0.5			ORGANIC SILT: low plasticity, dark brown.	M	VSt to H			TOPSOIL		
			VS >202 kPa		0.5 - 1.0			SILT: non plastic to low plasticity, orange brown, with trace fine grained sand. 0.35 m: with minor clay						VOLCANIC ASHES	
			VS 153/32 kPa		1.0 - 1.5			SAND: fine to medium grained, brown, with some silt. 1.1 m: with trace silt			L to MD				MATUA SUB-GROUP
			VS >202 kPa		1.5 - 2.0	VS 148/112 kPa		2.0			SILT: non plastic, pale brown, with minor fine grained sand.		VSt		
Hand Auger HAL354 terminated at 2.0 m Target depth															

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:40

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing penetration  water 	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	---	--	--	--

* bit shown by suffix
 e.g. AD/T
 B blank bit
 T TC bit
 V V bit

Engineering Log - Hand Auger



client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 356**

Borehole ID: **HAL356**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **30 May 2016**
 date completed: **30 May 2016**
 logged by: **ODS**
 checked by: **DBC**

position: E: 368456; N: 800038 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: SL588

drilling information				material substance										
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations	
HA N Not Encountered	1		VS >202 kPa					ORGANIC SILT: low plasticity, dark brown.	M	VSt to H			TOPSOIL	
	2		VS >202 kPa		0.5			SILT: non plastic to low plasticity, orange brown, with trace fine grained sand.					VOLCANIC ASHES	
	3		VS >202 kPa											
				VS >202 kPa		1.0								
				VS >202 kPa					SILT: low plasticity, orange, with trace clay and with trace fine to coarse grained sand. Greasy.					MATUA SUB-GROUP
				VS >202 kPa		1.5								
			VS >202 kPa		2.0			Hand Auger HAL356 terminated at 2.0 m Target depth						

CDF_0_9_06_LIBRARY_GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:40

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing penetration  water 	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	---	--	--	--

* bit shown by suffix
 e.g. AD/T
 B blank bit
 T TC bit
 V V bit

Engineering Log - Hand Auger


client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 358**

Borehole ID: **HAL358**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **30 May 2016**
 date completed: **30 May 2016**
 logged by: **NM**
 checked by: **DBC**

position: E: 368449; N: 800072 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: DR2244

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
HA N Not Encountered	1		VS >183 kPa				ML	ORGANIC SILT: low plasticity, dark brown.	M	VSt			TOPSOIL
	2		VS >183 kPa		0.5			SILT: low plasticity, orange brown, with trace fine grained sand, trace clay.	D to M				MATUA SUB-GROUP
	3		VS 107/19 kPa					0.7 m: minor fine grained sand with clay absent.	M				
			VS 81/19 kPa		1.0			0.9 m: some fine grained sand.		St			
			VS 94/19 kPa					1.1 m: minor fine grained sand.					
			VS 81/19 kPa		1.5			1.3 m: minor clay, trace fine grained sand.					
			VS 120/25 kPa				CL-ML	Clayey SILT: low plasticity, orange, with trace fine to medium grained sand, greasy.		VSt			
			VS >183 kPa		2.0			1.8 m: minor fine to medium grained sand.					
Hand Auger HAL358 terminated at 2.0 m Target depth													

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:40

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing penetration  no resistance ranging to refusal water 10-Oct-12 water level on date shown water inflow water outflow	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	--	--	--	--

* bit shown by suffix
 e.g. AD/T
 B blank bit
 T TC bit
 V V bit

Engineering Log - Hand Auger


client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 360**

Borehole ID: **HAL360**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **30 May 2016**
 date completed: **30 May 2016**
 logged by: **ODS/NM**
 checked by: **DBC**

position: E: 368445; N: 800106 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: SL588

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
HA N Not Encountered	1		VS >202 kPa					ORGANIC SILT: low plasticity, dark brown.	M	VSt to H			TOPSOIL
	2		VS 180/41 kPa		0.5			SILT: non plastic to low plasticity, orange brown, with trace fine grained sand.					VOLCANIC ASHES
	3		VS 190/39 kPa		1.0			0.6 m: with trace clay					
			VS 163/34 kPa		1.5			SILT: non plastic to low plasticity, orange, with trace clay and trace fine to coarse grained sand.					MATUA SUB-GROUP
			VS 175/74 kPa		1.5								
			VS >202 kPa		2.0								
			VS >202 kPa		2.0			Hand Auger HAL360 terminated at 2.0 m Target depth					

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:40

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing penetration  water 10-Oct-12 water level on date shown water inflow water outflow	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remouded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	--	---	--	--

* bit shown by suffix
 e.g. AD/T
 B blank bit
 T TC bit
 V V bit

Engineering Log - Hand Auger



client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 362**

Borehole ID: **HAL362**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **30 May 2016**
 date completed: **30 May 2016**
 logged by: **NM**
 checked by: **DBC**

position: E: 368446; N: 800140 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: DR2244

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
	1 2 3							SOIL TYPE: plasticity or particle characteristic, colour, secondary and minor components			remoulded peak		
			VS >183 kPa					ORGANIC SILT: low plasticity, dark brown.	M	VSt to H			TOPSOIL
			VS >183 kPa		0.5		ML	SILT: low plasticity, yellow brown, with minor fine grained sand, trace clay.	D				MATUA SUB-GROUP
			VS 169/31 kPa						D to M				
			VS 133/33 kPa		1.0				D				
			VS >183 kPa										
			VS 151/25 kPa		1.5			1.3 m: Some sand. Greasy					
			VS >183 kPa										
			VS >183 kPa		2.0			Hand Auger HAL362 terminated at 2.0 m Target depth					

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:40

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing penetration  no resistance ranging to refusal water  10-Oct-12 water level on date shown water inflow water outflow	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	---	--	--	--


* bit shown by suffix
 e.g. AD/T
 B blank bit
 T TC bit
 V V bit

Engineering Log - Hand Auger



client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 364**

Borehole ID: **HAL364**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **31 May 2016**
 date completed: **31 May 2016**
 logged by: **ODS**
 checked by: **DBC**

position: E: 368499; N: 800101 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: SL588

drilling information				material substance																				
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations											
method & support 1 penetration 2 3 HA N Not Encountered	VS >202 kPa VS 158/32 kPa VS 98/34 kPa VS 117/22 kPa VS 156/44 kPa VS >202 kPa	Not Encountered	VS >202 kPa VS 158/32 kPa VS 98/34 kPa VS 117/22 kPa VS 156/44 kPa VS >202 kPa	RL (m) depth (m) 0.5 1.0 1.5 2.0	graphic log 	classification symbol SOIL TYPE: plasticity or particle characteristic, colour, secondary and minor components ORGANIC SILT: low plasticity, dark brown. SILT: non plastic to low plasticity, orange brown, with trace fine grained sand. SILT: low plasticity, orange brown, with minor clay. 1.7 m: becoming non to slightly plastic, becoming orange, with trace fine to medium grained sand, greasy	moisture condition M St VSt to H	consistency / relative density VSt to H St VSt to H	vane shear (kPa) peak remoulded 50 100 150 200 0 10 20 30 40 50 60 70 80 90 100	DCP (blows/100 mm) 2 4 6 8 10	structure and additional observations TOPSOIL VOLCANIC ASHES MATUA SUB-GROUP													
												Hand Auger HAL364 terminated at 2.0 m Target depth												

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:40

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
* bit shown by suffix e.g. AD/T B blank bit T TC bit V V bit	penetration  no resistance ranging to refusal	moisture D dry M moist W wet Wp plastic limit Wl liquid limit	water  10-Oct-12 water level on date shown water inflow water outflow	

Engineering Log - Hand Auger



client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 366**

Borehole ID: **HAL366**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **31 May 2016**
 date completed: **31 May 2016**
 logged by: **NM**
 checked by: **DBC**

position: E: 368504; N: 800069 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: DR2244

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
HA N Not Encountered	1		VS >183 kPa					ORGANIC SILT: low plasticity, dark brown.	D	VSt			TOPSOIL
	2		VS 169/26 kPa		0.5		ML	SILT: low plasticity, yellow brown, with trace fine grained sand, trace clay.	M				VOLCANIC ASHES
	3		VS 169/31 kPa										
				VS 183/32 kPa		1.0							
			VS 151/31 kPa										
			VS 94/21 kPa		1.5		ML	SILT: low plasticity, orange, with minor to trace clay, trace fine to coarse grained sand. Greasy.		St			MATUA SUB-GROUP
			VS 151/31 kPa										
			VS >183 kPa		2.0								
Hand Auger HAL366 terminated at 2.0 m Target depth													

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:40

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
* bit shown by suffix e.g. AD/T B blank bit T TC bit V V bit	penetration 	moisture D dry M moist W wet Wp plastic limit Wl liquid limit	water 10-Oct-12 water level on date shown 	

Engineering Log - Hand Auger


client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 368**

Borehole ID: **HAL368**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **31 May 2016**
 date completed: **31 May 2016**
 logged by: **NM**
 checked by: **DBC**

position: E: 368508; N: 800025 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: DR2244

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
method & support: 1 penetration 2 3 HA N Not Encountered	VS >183 kPa VS 169/31 kPa VS 169/31 kPa VS 169/31 kPa VS 61/21 kPa VS >183 kPa	Not Encountered	VS >183 kPa VS 169/31 kPa VS 169/31 kPa VS 169/31 kPa VS 61/21 kPa VS >183 kPa	RL (m) depth (m) 0.5 1.0 1.5 2.0	graphic log ML ML ML ML ML	classification symbol SOIL TYPE: plasticity or particle characteristic, colour, secondary and minor components ORGANIC SILT: low plasticity, dark brown. SILT: low plasticity, orange brown, with minor fine grained sand, trace clay. 0.6 m: becoming minor clay, trace fine to medium grained sand. 1.1 m: becoming orange with minor clay, trace fine to medium grained sand, greasy. 1.6 m: minor fine to medium grained sand. Compressible 1.9 m: some fine to medium grained sand.	moisture condition D M W VSt to H	consistency / relative density VSt St H	vane shear (kPa) peak remoulded peak	DCP (blows/100 mm) 2 4 6 8 10	structure and additional observations TOPSOIL MATUA SUB-GROUP		
												Hand Auger HAL368 terminated at 2.0 m Target depth	

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:40

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing penetration  10-Oct-12 water level on date shown water inflow water outflow	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	--	--	--	--

* bit shown by suffix
 e.g. AD/T
 B blank bit
 T TC bit
 V V bit

Engineering Log - Hand Auger


client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 370**

Borehole ID: **HAL370**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **31 May 2016**
 date completed: **31 May 2016**
 logged by: **ODS**
 checked by: **DBC**

position: E: 368540; N: 800036 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: SL588

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
HA N Not Encountered	1		VS >202 kPa					ORGANIC SILT: low plasticity, dark brown.	M	VSt			TOPSOIL
	2		VS >202 kPa		0.5			SILT: non plastic to low plasticity, orange brown, with trace fine grained sand.			⊕		VOLCANIC ASHES
	3		VS >202 kPa		1.0						⊕		
				VS 153/44 kPa		1.5			SILT: non plastic, pale orange brown, with minor fine to coarse grained sand. Greasy.			⊕	
			VS >202 kPa		2.0			Hand Auger HAL370 terminated at 2.0 m Target depth					

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:40

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing penetration  no resistance ranging to refusal water 10-Oct-12 water level on date shown water inflow water outflow	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	--	--	--	--

* bit shown by suffix
 e.g. AD/T
 B blank bit
 T TC bit
 V V bit

Engineering Log - Hand Auger



client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 372**

Borehole ID: **HAL372**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **31 May 2016**
 date completed: **31 May 2016**
 logged by: **NM**
 checked by: **DBC**

position: E: 368572; N: 800036 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: DR2244

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
HA N Not Encountered	1							ORGANIC SILT: low plasticity, dark brown.	M	VSt to H			TOPSOIL
	2		VS >183 kPa		0.5		ML	SILT: low plasticity, orange brown, with minor fine to medium grained sand.	D				VOLCANIC ASHES
	3		VS >183 kPa										
				VS >183 kPa									
			VS 169/31 kPa		1.0		ML	SILT: low plasticity, yellow brown, with minor clay, trace fine grained sand.	M	VSt			MATUA SUB-GROUP
			VS 151/25 kPa										
			VS 169/25 kPa		1.5								
			VS 133/31 kPa										
			VS 151/19 kPa		2.0								
Hand Auger HAL372 terminated at 2.0 m Target depth													

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:40

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing penetration  water 	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	---	--	--	--

* bit shown by suffix
 e.g. AD/T
 B blank bit
 T TC bit
 V V bit

Engineering Log - Hand Auger



client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 374**

Borehole ID: **HAL374**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **31 May 2016**
 date completed: **31 May 2016**
 logged by: **ODS**
 checked by: **DBC**

position: E: 368605; N: 800029 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: SL588

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
method & support 1 penetration 2 3 HA N Not Encountered			VS >202 kPa		0.5			ORGANIC SILT: low plasticity, dark brown.	M	VSt to H	vane shear ⊕ remoulded ⊙ peak (kPa) 50 100 150 200	DCP (blows/100 mm) 2 4 6 8 10	TOPSOIL
			VS 173/ 52 kPa					SILT: non plastic to low plasticity, orange brown, with trace fine grained sand.					VOLCANIC ASHES
			VS 165/ 46 kPa										
			VS 102/ 29 kPa										
			VS 165/ 39 kPa		1.5								
			VS 170/ 38 kPa		2.0								
Hand Auger HAL374 terminated at 2.0 m Target depth													

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:40

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing penetration  no resistance ranging to refusal water  10-Oct-12 water level on date shown water inflow water outflow	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	---	--	--	--

* bit shown by suffix
 e.g. AD/T
 B blank bit
 T TC bit
 V V bit


Engineering Log - Hand Auger

client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 376**

Borehole ID: **HAL376**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **31 May 2016**
 date completed: **31 May 2016**
 logged by: **ODS**
 checked by: **DBC**

position: E: 368640; N: 800018 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: SL588

drilling information				material substance										
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations	
method & support: HA hand auger N nil	penetration: no resistance ranging to refusal	water: Not Encountered	VS >202 kPa		0.5			ORGANIC SILT: low plasticity, dark brown.	M	VSt to H	50 100 150 200	2 4 6 8 10	TOPSOIL	
			VS 177/ 34 kPa					SILT: non plastic to low plasticity, orange brown, with trace fine grained sand.			50 100 150 200	2 4 6 8 10	VOLCANIC ASHES	
			VS 156/ 35 kPa			1.0			SILT: non plastic to low plasticity, pale orange brown, with trace to minor fine to coarse grained sand and with trace clay.			50 100 150 200	2 4 6 8 10	MATUA SUB-GROUP
			VS 133/ 32 kPa			1.5			SILT: non plastic to low plasticity, pale orange brown, with trace to minor fine to coarse grained sand and with trace clay.			50 100 150 200	2 4 6 8 10	
			VS 102/ 46 kPa		1.8			1.8 m: with some fine to coarse grained sand			50 100 150 200	2 4 6 8 10		
			VS >202 kPa		2.0			Hand Auger HAL376 terminated at 2.0 m Target depth			50 100 150 200	2 4 6 8 10		

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud C casing N nil	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
moisture D dry M moist W wet Wp plastic limit Wl liquid limit	penetration  no resistance ranging to refusal	water 10-Oct-12 water level on date shown water inflow water outflow		

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:40

Engineering Log - Hand Auger


client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 378**

Borehole ID: **HAL378**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **31 May 2016**
 date completed: **31 May 2016**
 logged by: **ODS**
 checked by: **DBC**

position: E: 368670; N: 800001 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: SL588

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
method & support: 1 penetration 2 3 HA N Not Encountered	VS >202 kPa VS 156/ 24 kPa VS 98/ 21 kPa VS 96/ 18 kPa VS 79/ 21 kPa VS >202 kPa	Not Encountered	VS >202 kPa VS 156/ 24 kPa VS 98/ 21 kPa VS 96/ 18 kPa VS 79/ 21 kPa VS >202 kPa	RL (m) depth (m) 0.5 1.0 1.5 2.0	graphic log (wavy line for organic silt, vertical lines for silt)	classification symbol M, St, H	material description ORGANIC SILT: low plasticity, dark brown. SILT: non plastic, pale orange brown, with minor fine to coarse grained sand. 0.6 m: with some fine to coarse grained sand 1.1 m: becoming pale brown, with trace fine to coarse grained sand and with trace clay. Sticky	moisture condition M, St, H	consistency / relative density VSt to H, St, H	vane shear (kPa) (circles with numbers)	DCP (blows/100 mm) (vertical bars)	TOPSOIL	MATUA SUB-GROUP
												Hand Auger HAL378 terminated at 2.0 m Target depth	

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:40

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing penetration  no resistance ranging to refusal water 10-Oct-12 water level on date shown water inflow water outflow	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	--	--	--	--

* bit shown by suffix
 e.g. AD/T
 B blank bit
 T TC bit
 V V bit

Engineering Log - Hand Auger



client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 380**

Borehole ID: **HAL380**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **31 May 2016**
 date completed: **31 May 2016**
 logged by: **ODS**
 checked by: **DBC**

position: E: 368699; N: 799951 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: SL588

drilling information				material substance											
method & support	1 penetration	2 penetration	3 penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
HA	N			Not Encountered	VS 173/ 38 kPa	0.5				ORGANIC SILT: low plasticity, dark brown.	M	VSt to H			TOPSOIL
					VS 108/ 26 kPa					SILT: non plastic, brown, with minor fine to coarse grained sand.				MATUA SUB-GROUP	
					VS 189/ 19 kPa	1.0				0.6 m: becoming orange brown, with trace clay. Greasy					
					VS 106/ 19 kPa					1.5				0.9 m: clay absent	
					VS >202 kPa	2.0									
					VS >202 kPa										
Hand Auger HAL380 terminated at 2.0 m Target depth															

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:40











method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remouded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
* bit shown by suffix e.g. AD/T B blank bit T TC bit V V bit	penetration 	moisture D dry M moist W wet Wp plastic limit Wl liquid limit	water 	

Engineering Log - Hand Auger



client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 382**

Borehole ID: **HAL382**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **31 May 2016**
 date completed: **31 May 2016**
 logged by: **NM**
 checked by: **DBC**

position: E: 368706; N: 799921 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: DR2244

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
method & support: HA hand auger N nil Not Encountered	1 2 3 penetration	Not Encountered	VS >183 kPa	RL (m) depth (m) 0.5 1.0 1.5 2.0	depth (m)		classification symbol	ORGANIC SILT: low plasticity, dark brown.	M	VSt			TOPSOIL MATUA SUB-GROUP
			VS >183 kPa					SILT: low plasticity, yellow brown, with minor fine to medium grained sand, trace clay.	M to W				
			VS 151/ 37 kPa					Sandy SILT: non plastic, orange brown, with fine to medium grained sand.	St				
			VS 126/ 31 kPa					SILT: low plasticity, yellow brown, with minor fine to medium grained sand, trace clay.	St				
			VS 94/ 31 kPa						VSt				
			VS 94/ 31 kPa					1.7 m: becoming red brown.	St				
			VS 120/ 31 kPa					1.9 m: becoming yellow brown with minor clay, trace fine grained sand.					
			VS 81/ 34 kPa					Hand Auger HAL382 terminated at 2.0 m Target depth					

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:40

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud C casing N nil	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
penetration  no resistance ranging to refusal		moisture D dry M moist W wet Wp plastic limit Wl liquid limit		
water  10-Oct-12 water level on date shown water inflow water outflow				


* bit shown by suffix
 e.g. AD/T
 B blank bit
 T TC bit
 V V bit

Engineering Log - Hand Auger



client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 383**

Borehole ID: **HAL383**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **09 Jun 2016**
 date completed: **09 Jun 2016**
 logged by: **ODS**
 checked by: **DBC**

position: E: 368728; N: 799928 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: SL588

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
HA N Not Encountered	1 2 3	VS >202 kPa VS >202 kPa VS UTP VS >202 kPa VS >202 kPa	VS >202 kPa VS >202 kPa VS UTP VS >202 kPa VS >202 kPa	0.5 1.0 1.5 2.0		SOIL TYPE: plasticity or particle characteristic, colour, secondary and minor components	D to M H M	ORGANIC SILT: low plasticity, dark brown.	consistency / relative density 50 100 150 200	vane shear ◉ remoulded ◉ peak (kPa)	DCP (blows/100 mm)	TOPSOIL	
								SAND: fine to coarse grained, yellow-brown.				MATUA SUB-GROUP	
								SILT: non plastic to low plasticity, brown, with trace fine grained sand.				VS UTP VS UTP	
Hand Auger HAL383 terminated at 2.0 m Target depth													

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:40

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
* bit shown by suffix e.g. AD/T B blank bit T TC bit V V bit	penetration  no resistance ranging to refusal	moisture D dry M moist W wet Wp plastic limit Wl liquid limit	water  10-Oct-12 water level on date shown water inflow water outflow	

Engineering Log - Hand Auger



client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 384**

Borehole ID: **HAL384A**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **31 May 2016**
 date completed: **31 May 2016**
 logged by: **NM**
 checked by: **DBC**

position: E: 368748; N: 799926 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: DR2244

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
HA	N	Not Encountered	VS > 183 kPa	-	0.5	[Symbol]	ML	ORGANIC SILT: low plasticity, dark brown.	D	VSt	⊕		TOPSOIL
			VS 74/ 19 kPa					0.4 m: becoming orange with some clay, trace fine grained silt, sticky and greasy.	W	St	⊕ ⊕		MATUA SUB-GROUP
			VS 68/ 19 kPa					0.8 m: occasional pockets of manganese.			⊕ ⊕		
			VS 74/ 19 kPa		1.0						⊕ ⊕		
			VS 55/ 19 kPa								⊕ ⊕		
			VS 74/ 19 kPa		1.5						⊕ ⊕		
			VS 68/ 19 kPa								⊕ ⊕		
			VS 68/ 19 kPa		2.0			Hand Auger HAL384A terminated at 2.0 m Target depth			⊕ ⊕		

CDF_0_9_06_LIBRARY.GLB rev: AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS: GPJ <<DrawingFile>> 21/06/2016 11:40

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing penetration  water 	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	---	--	--	--

* bit shown by suffix
 e.g. AD/T
 B blank bit
 T TC bit
 V V bit

Engineering Log - Hand Auger



client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 384**

Borehole ID: **HAL384B**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **09 Jun 2016**
 date completed: **09 Jun 2016**
 logged by: **ODS**
 checked by: **DBC**

position: E: 368748; N: 799921 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: SL588

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
HA N Not Encountered	1 2 3	Not Encountered	VS >202 kPa					ORGANIC SILT: low plasticity, dark brown.	M	VSt to H			TOPSOIL
			VS 139/24 kPa		0.5		SILT: non plastic to low plasticity, orange, with trace fine to coarse grained sand. Greasy. 0.5 m: with trace clay						MATUA SUB-GROUP
			VS 156/29 kPa										
			VS 74/28 kPa							St			
			VS 62/25 kPa					1.4 m: becomes sticky					
			VS 61/29 kPa										
					2.0			Hand Auger HAL384B terminated at 2.0 m Target depth					

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:40

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
* bit shown by suffix e.g. AD/T B blank bit T TC bit V V bit	penetration  water 	moisture D dry M moist W wet Wp plastic limit Wl liquid limit		

Engineering Log - Hand Auger



client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 385**

Borehole ID: **HAL385**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **09 Jun 2016**
 date completed: **09 Jun 2016**
 logged by: **ODS**
 checked by: **DBC**

position: E: 368731; N: 799900 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: SL588

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
	1 2 3							SOIL TYPE: plasticity or particle characteristic, colour, secondary and minor components			remoulded peak		
								ORGANIC SILT: low plasticity, dark brown.	M	H			TOPSOIL
			VS >202 kPa		0.5			SILT: non plastic to low plasticity, dark orange brown, with trace fine grained sand.					VOLCANIC ASHES
			VS >202 kPa										
			VS >202 kPa		1.0			1.0 m: becoming orange brown					
			VS >202 kPa										
			VS >202 kPa		1.5			1.5 m: with trace clay, becoming slightly plastic					
			VS >202 kPa										
			VS >202 kPa		2.0			Hand Auger HAL385 terminated at 2.0 m Target depth					

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:40



method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
* bit shown by suffix e.g. AD/T B blank bit T TC bit V V bit	penetration 	moisture D dry M moist W wet Wp plastic limit Wl liquid limit		
water 10-Oct-12 water level on date shown 				

Engineering Log - Hand Auger



client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 386**

Borehole ID: **HAL386**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **31 May 2016**
 date completed: **31 May 2016**
 logged by: **ODS**
 checked by: **DBC**

position: E: 368708; N: 799898 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: SL588

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
HA N Not Encountered	1 2 3	VS >202 kPa VS >202 kPa VS >202 kPa VS >202 kPa	VS >202 kPa VS >202 kPa VS >202 kPa VS >202 kPa	0 0.5 1.0 1.5 2.0	0 0.5 1.0 1.5 2.0		SOIL TYPE: plasticity or particle characteristic, colour, secondary and minor components	ORGANIC SILT: low plasticity, dark brown.	M	VS to H	50 100 150 200		TOPSOIL
								SILT: non plastic to low plasticity, orange brown, with trace to minor clay and trace fine grained sand. 0.4 m: becoming greasy					MATUA SUB-GROUP
								SILTY SAND: fine to coarse grained, pale brown.	MD to D				
								Clayey SILT: low plasticity, pale brown, with trace fine grained sand.	L	VS to H			
			VS >202 kPa	2.0	2.0			Hand Auger HAL386 terminated at 2.0 m Target depth					

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:40

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing penetration  no resistance ranging to refusal water  10-Oct-12 water level on date shown water inflow water outflow	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	---	--	--	--



* bit shown by suffix
 e.g. AD/T
 B blank bit
 T TC bit
 V V bit

Engineering Log - Hand Auger

client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 387**

Borehole ID: **HAL387**
 sheet: 1 of 1
 project no. **GENZTAUC13086AP**
 date started: **09 Jun 2016**
 date completed: **09 Jun 2016**
 logged by: **ODS**
 checked by: **DBC**

position: E: 368709; N: 799882 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: SL588

drilling information				material substance											
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations		
HA N Not Encountered VS UTP VS 182/52 kPa VS >202 kPa VS >202 kPa			VS 185/19 kPa					ORGANIC SILT: low plasticity, dark brown.	M		50, 100, 150, 200		TOPSOIL		
			VS 133/24 kPa		0.5			SILT: low plasticity, orange brown, with trace fine to medium grained sand and with trace clay. Greasy.		VSt to H	⊕, ⊙			MATUA SUB-GROUP	
			VS >202 kPa		1.0			0.9 m: with some fine to coarse grained sand				⊕, ⊙			
			VS UTP		1.2			1.2 m: becoming grey brown							
			VS 182/52 kPa		1.5			1.4 m: with some fine grained sand							
			VS >202 kPa		2.0					SILTY SAND: fine to coarse grained, grey brown.	MD				
								SILT: non plastic to low plasticity, grey brown, with trace to minor fine to coarse grained sand.	H						
								1.8 m: becoming brown and non plastic							
Hand Auger HAL387 terminated at 2.0 m Target depth															

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud C casing N nil	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
moisture D dry M moist W wet Wp plastic limit Wl liquid limit				


CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:41

Engineering Log - Hand Auger


client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 388**

Borehole ID: **HAL388A**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **31 May 2016**
 date completed: **31 May 2016**
 logged by: **ODS**
 checked by: **DBC**

position: E: 368706; N: 799869 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: SL588

drilling information				material substance																						
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations													
method & support: 1 penetration 2 3 HA N Not Encountered	VS 144/ 24 kPa VS >202 kPa VS 71/ 21 kPa VS 49/ 34 kPa VS 63/ 29 kPa VS >202 kPa	Not Encountered	VS 144/ 24 kPa VS >202 kPa VS 71/ 21 kPa VS 49/ 34 kPa VS 63/ 29 kPa VS >202 kPa	RL (m) 0.5 1.0 1.5 2.0	depth (m) 0.5 1.0 1.5 2.0	graphic log 	classification symbol M St F St H	material description ORGANIC SILT: low plasticity, dark brown. SILT: non plastic to low plasticity, orange brown, with trace to minor clay and trace fine to coarse grained sand. 0.7 m: pale brown, with trace clay and with minor fine to coarse grained sand 0.85 m: becoming sticky 1.3 m: with some fine to coarse grained sand 1.8 m: becoming brown, with trace fine grained sand, clay absent	moisture condition M St F St H	consistency / relative density VS to H St F St H	vane shear (kPa) 100 150 200	DCP (blows/100 mm) 2 4 6 8 10	structure and additional observations TOPSOIL MATUA SUB-GROUP													
														Hand Auger HAL388A terminated at 2.0 m Target depth												

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:41


method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger * bit shown by suffix e.g. AD/T B blank bit T TC bit V V bit	support M mud N nil C casing penetration  no resistance ranging to refusal water 10-Oct-12 water level on date shown water inflow water outflow	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	--	--	--	--

Engineering Log - Hand Auger



client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 388**

Borehole ID: **HAL388B**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **09 Jun 2016**
 date completed: **09 Jun 2016**
 logged by: **ODS**
 checked by: **DBC**

position: E: 368706; N: 799865 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: SL588

drilling information				material substance																					
method & support	1 penetration	2	3	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations										
HA N Not Encountered	1 2 3	VS 184/ 46 kPa VS >202 kPa VS 180/ 44 kPa VS >202 kPa VS >202 kPa VS >202 kPa	0.5 1.0 1.5 2.0		SOIL TYPE: plasticity or particle characteristic, colour, secondary and minor components	M VS to H MD MD to D MD H	50 100 150 200 250 300 350 400 450 500	0 1 2 3 4 5 6 7 8 9 10	TOPSOIL MATUA SUB-GROUP																
										ORGANIC SILT: low plasticity, dark brown.															
										SILT: non plastic to low plasticity, orange brown with mottled brown, with trace fine to medium grained sand.															
										SAND: fine to coarse grained, orange brown, with trace silt.															
										SILT: non plastic, orange brown, with trace fine to coarse grained sand.															
										SAND: fine to coarse grained, yellow brown, with trace silt. SILTY SAND: fine grained, yellow brown.															
										SAND: fine to coarse grained, brown grey, with lenses of grey clayey silt.															
SILT: non plastic, brown, with trace fine grained sand.																									
Hand Auger HAL388B terminated at 2.0 m Target depth																									

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS.GPJ <<DrawingFile>> 21/06/2016 11:41

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System	consistency / relative density VS very soft S soft F firm St stiff VS stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
* bit shown by suffix e.g. AD/T B blank bit T TC bit V V bit	penetration  no resistance ranging to refusal	moisture D dry M moist W wet Wp plastic limit Wl liquid limit	water  10-Oct-12 water level on date shown water inflow water outflow	

Engineering Log - Hand Auger



client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 389**

Borehole ID: **HAL389**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **09 Jun 2016**
 date completed: **09 Jun 2016**
 logged by: **ODS**
 checked by: **DBC**

position: E: 368704; N: 799852 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: SL588

drilling information				material substance										
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations	
HA N Not Encountered	1		VS >202 kPa					ORGANIC SILT: low plasticity, dark brown.	M	H			TOPSOIL	
	2		VS >202 kPa		0.5			SILT: non plastic to low plasticity, brown, with trace fine grained sand and with trace clay.			⊙		VOLCANIC ASHES	
	3		VS >202 kPa					0.6 m: clay becomes absent			⊙			
				VS >202 kPa		1.0			0.9 m: becoming orange brown			⊙		
				VS >202 kPa		1.5			1.0 m: with trace clay, sand becomes absent			⊙		
			VS >202 kPa		2.0			Hand Auger HAL389 terminated at 2.0 m Target depth			⊙			

CDF_0_9_06_LIBRARY.GLB rev: AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS.GPJ <<DrawingFile>> 21/06/2016 11:41

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing penetration  water 	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	---	--	--	--


* bit shown by suffix
 e.g. AD/T
 B blank bit
 T TC bit
 V V bit

Engineering Log - Hand Auger


client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 390**

Borehole ID: **HAL390**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **31 May 2016**
 date completed: **31 May 2016**
 logged by: **ODS**
 checked by: **DBC**

position: E: 368698; N: 799838 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: SL588

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
	1 2 3							ORGANIC SILT: low plasticity, dark brown.	M	H			TOPSOIL
			VS >202 kPa					Clayey SILT: low plasticity, pink brown with mottled grey and mottled dark brown, with trace fine to coarse grained sand.			⊙		FILL
			VS UTP		0.5			SILT: low plasticity, orange brown, with minot clay and with trace fine to coarse grained sand.					MATUA SUB-GROUP
			VS >202 kPa					Sandy SILT: non plastic, brown to pale brown, sand is fine to coarse grained.			VS UTP		
			VS >202 kPa					SILT: non plastic to low plasticity, orange brown, with trace fine grained sand and with trace clay.			⊙		
			VS >202 kPa		1.0						⊙		
			VS >202 kPa								⊙		
			VS >202 kPa		1.5						⊙		
			VS >202 kPa								⊙		
			VS >202 kPa		2.0						⊙		
								Hand Auger HAL390 terminated at 2.0 m Target depth					

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:41

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing penetration  no resistance ranging to refusal water 10-Oct-12 water level on date shown water inflow water outflow	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	--	--	--	--

* bit shown by suffix
 e.g. AD/T
 B blank bit
 T TC bit
 V V bit

Engineering Log - Hand Auger


client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 392**

Borehole ID: **HAL392**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **31 May 2016**
 date completed: **31 May 2016**
 logged by: **ODS**
 checked by: **DBC**

position: E: 368704; N: 799808 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: SL588

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
HA N Not Encountered	1							ORGANIC SILT: low plasticity, dark brown.	M	VSt to H			TOPSOIL
	2		VS >202 kPa		0.5			SILT: non plastic to low plasticity, brown with mottled pale brown and grey, with trace to minor fine to medium grained sand and with trace clay.			⊕		FILL
	3		VS >202 kPa								⊕		
				VS 158/49 kPa		1.0			SILT: low plasticity, orange brown, with minor clay and trace fine grained sand.			⊕	
			VS >202 kPa		1.5			1.3 m: becoming greasy			⊕		
			VS >202 kPa		2.0			Hand Auger HAL392 terminated at 2.0 m Target depth			⊕		

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:41

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing penetration  no resistance ranging to refusal water 10-Oct-12 water level on date shown water inflow water outflow	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	--	--	--	--

* bit shown by suffix
 e.g. AD/T
 B blank bit
 T TC bit
 V V bit

Engineering Log - Hand Auger


client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 394**

Borehole ID: **HAL394**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **31 May 2016**
 date completed: **31 May 2016**
 logged by: **NM**
 checked by: **DBC**

position: E: 368686; N: 799786 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: DR2244

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
	1 2 3							SOIL TYPE: plasticity or particle characteristic, colour, secondary and minor components			remoulded peak		
			VS >183 kPa					ORGANIC SILT: low plasticity, dark brown.	D	VSt to H			TOPSOIL
			VS >183 kPa		0.5		ML	SILT: low plasticity, orange brown mottled with, with some clay, trace fine grained sand.					MATUA SUB-GROUP
			VS UTP				ML	Sandy SILT: non plastic, white, with fine grained sand.			VS UTP		
			VS >183 kPa		1.0		ML	SILT: low to medium plasticity, orange brown, with some clay, trace fine grained sand.					
			VS >183 kPa				ML	SILT: low to medium plasticity, orange brown, with some clay, trace fine grained sand.					
			VS UTP		1.5			1.2 m: soil is friable.			VS UTP		
			VS UTP								VS UTP		
			VS UTP		2.0						VS UTP		
Hand Auger HAL394 terminated at 2.0 m Target depth													

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:41

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing penetration  no resistance ranging to refusal water 10-Oct-12 water level on date shown water inflow water outflow	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	--	--	--	--

* bit shown by suffix
 e.g. AD/T
 B blank bit
 T TC bit
 V V bit

Engineering Log - Hand Auger



client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 396**

Borehole ID: **HAL396**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **31 May 2016**
 date completed: **31 May 2016**
 logged by: **NM**
 checked by: **DBC**

position: E: 368660; N: 799790 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: DR2244

drilling information				material substance											
method & support	1 penetration	2 penetration	3 penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
					VS >183 kPa		0.5			SILT: low to medium plasticity, red brown, with trace fine to medium grained sand. 0.3 m: soil is friable.	D	VSt to H	VS UTP		MATUA SUB-GROUP
				Not Encountered	VS >183 kPa		1.0						VS UTP		
					VS >183 kPa		1.5		ML	SILT: low plasticity, yellow orange, with some clay, trace fine grained sand.	M				
					VS >183 kPa		2.0								
					VS >183 kPa		2.0			Hand Auger HAL396 terminated at 2.0 m Target depth					

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:41

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing penetration  no resistance ranging to refusal water  10-Oct-12 water level on date shown water inflow water outflow	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	---	--	--	--




* bit shown by suffix
 e.g. AD/T
 B blank bit
 T TC bit
 V V bit

Engineering Log - Hand Auger



client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 398**

Borehole ID: **HAL398**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **30 May 2016**
 date completed: **30 May 2016**
 logged by: **NM**
 checked by: **DBC**

position: E: 368652; N: 799844 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: DR2244

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
method & support: 1 penetration 2 3 HA N Not Encountered	VS >183 kPa VS >183 kPa VS >183 kPa VS >183 kPa VS >183 kPa VS >183 kPa	VS >183 kPa VS >183 kPa VS >183 kPa VS >183 kPa VS >183 kPa VS >183 kPa	VS >183 kPa VS >183 kPa VS >183 kPa VS >183 kPa VS >183 kPa VS >183 kPa	0.5 1.0 1.5 2.0	ML ML ML ML ML ML		ML ML ML ML ML ML	ORGANIC SILT: low plasticity, dark brown.	D	VSt to H			TOPSOIL
								SILT: low plasticity, orange brown, with trace fine to medium grained sand, trace clay.					MATUA SUB-GROUP
								0.6 m: some clay.					
								1.0 m: a 100mm lense of pale yellow fine to medium grained sand with minor silt is present.					
								1.1 m: with minor fine grained sand, trace clay.					
								1.5 m: with minor clay, trace fine grained sand.					
Hand Auger HAL398 terminated at 2.0 m Target depth													

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:41

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
* bit shown by suffix e.g. AD/T B blank bit T TC bit V V bit	penetration  water 	moisture D dry M moist W wet Wp plastic limit Wl liquid limit		

Engineering Log - Hand Auger


client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 400**

Borehole ID: **HAL400**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **30 May 2016**
 date completed: **30 May 2016**
 logged by: **ODS**
 checked by: **DBC**

position: E: 368665; N: 799877 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: SL588

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
	1 2 3							SOIL TYPE: plasticity or particle characteristic, colour, secondary and minor components			remoulded peak		
			VS >202 kPa					ORGANIC SILT: low plasticity, dark brown.	D to M	VSt to H			TOPSOIL
			VS >202 kPa		0.5			SILT: non plastic, orange brown, with trace fine to coarse grained sand.					VOLCANIC ASHES
			VS >202 kPa					0.6 m: becoming slightly plastic	M				
			VS >202 kPa					0.75 m: becoming mottled pale brown					
			VS 165/38 kPa		1.0			1.0 m: with minor clay					
			VS >202 kPa					SILT: non plastic to low plasticity, brown with mottled pale brown and orange brown, with trace to minor fine to coarse grained sand.					MATUA SUB-GROUP
			VS >202 kPa		1.5								
			VS 158/41 kPa					1.7 m: with trace clay					
			VS 104/46 kPa		2.0			1.75 m: becoming brown					
								Hand Auger HAL400 terminated at 2.0 m Target depth					

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:41

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing penetration  no resistance ranging to refusal water 10-Oct-12 water level on date shown water inflow water outflow	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	--	--	--	--


* bit shown by suffix
 e.g. AD/T
 B blank bit
 T TC bit
 V V bit

Engineering Log - Hand Auger


client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 402**

Borehole ID: **HAL402**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **30 May 2016**
 date completed: **30 May 2016**
 logged by: **NM**
 checked by: **DBC**

position: E: 368665; N: 799916 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: DR2244

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
method & support: 1 penetration 2 3 HA N Not Encountered	VS > 183 kPa VS > 183 kPa VS > 183 kPa VS 151/25 kPa VS > 183 kPa VS > 183 kPa VS > 183 kPa	Not Encountered	VS > 183 kPa VS > 183 kPa VS > 183 kPa VS 151/25 kPa VS > 183 kPa VS > 183 kPa VS > 183 kPa	RL (m) 0.5 1.0 1.5 2.0	depth (m) 0.5 1.0 1.5 2.0	graphic log 	ML SILT: low plasticity, orange brown, with minor fine grained sand, trace clay.	D VS to H	consistency / relative density VS to H	vane shear (kPa) peak remoulded	DCP (blows/100 mm)	TOPSOIL	
							ML SILT: low plasticity, orange brown, with minor fine grained sand, trace clay.	M	consistency / relative density M	vane shear (kPa) peak remoulded	DCP (blows/100 mm)	VOLCANIC ASHES	
							ML SILT: low plasticity, orange brown, with some clay, minor fine to medium grained sand.	M to W	consistency / relative density M to W	vane shear (kPa) peak remoulded	DCP (blows/100 mm)	MATUA SUB-GROUP	
							ML SILT: low plasticity, orange brown, with some clay, minor fine to medium grained sand.	M to W	consistency / relative density M to W	vane shear (kPa) peak remoulded	DCP (blows/100 mm)	MATUA SUB-GROUP	
							ML SILT: low plasticity, orange brown, with some clay, minor fine to medium grained sand.	M to W	consistency / relative density M to W	vane shear (kPa) peak remoulded	DCP (blows/100 mm)	MATUA SUB-GROUP	
Hand Auger HAL402 terminated at 2.0 m Target depth													

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:41

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
* bit shown by suffix e.g. AD/T B blank bit T TC bit V V bit	penetration  no resistance ranging to refusal	moisture D dry M moist W wet Wp plastic limit Wl liquid limit	water 10-Oct-12 water level on date shown water inflow water outflow	

Engineering Log - Hand Auger



client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 404**

Borehole ID: **HAL404**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **30 May 2016**
 date completed: **30 May 2016**
 logged by: **ODS**
 checked by: **DBC**

position: E: 368648; N: 799955 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: SL588

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
HA N Not Encountered	1							ORGANIC SILT: low plasticity, dark brown.	D to M	VSt to H			TOPSOIL
	2		VS >202 kPa					SILT: non plastic to low plasticity, pale brown, with trace to minor fine to coarse grained sand and with trace clay.					FILL
	3		VS >202 kPa		0.5			SILT: non plastic to low plasticity, orange brown, with trace fine grained sand.	M				VOLCANIC ASHES
				VS >202 kPa		1.0		1.0 m: with trace clay					
				VS >202 kPa		1.5							
				VS >202 kPa		2.0			SILT: non plastic, brown, with trace to minor fine to coarse grained sand.				
			VS >202 kPa		2.0			Hand Auger HAL404 terminated at 2.0 m Target depth					

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:41

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing penetration  water 	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	---	--	--	--

* bit shown by suffix
 e.g. AD/T
 B blank bit
 T TC bit
 V V bit

Engineering Log - Hand Auger


client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 406**

Borehole ID: **HAL406**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **30 May 2016**
 date completed: **30 May 2016**
 logged by: **NM**
 checked by: **DBC**

position: E: 368624; N: 799974 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: DR2244

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
	1 2 3							SOIL TYPE: plasticity or particle characteristic, colour, secondary and minor components			50 100 150 200	2 4 6 8 10	
			VS >183 kPa					ORGANIC SILT: low plasticity, dark brown.	M	VSt to H			TOPSOIL
			VS >183 kPa		0.5		ML	SILT: low plasticity, orange brown, with minor clay, trace fine grained sand.	D		⊙		MATUA SUB-GROUP
			VS >183 kPa										
			VS UTP		1.0		SP	SAND: fine to medium grained, pale yellow brown, with some silt.			VS UTP		
			VS 151/21 kPa				ML	Sandy SILT: non plastic to low plasticity, pale yellow brown, with fine to medium grained sand.			⊙		
			VS >183 kPa		1.5		ML	SILT: low plasticity, pale yellow brown, with minor fine to medium grained sand, trace clay.	M to W		⊙		
			VS >183 kPa				ML	Sandy SILT: non plastic to low plasticity, pale yellow brown, with fine to medium grained sand.			⊙		
			VS >183 kPa		2.0			Hand Auger HAL406 terminated at 2.0 m Target depth			⊙		

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:41


method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
* bit shown by suffix e.g. AD/T B blank bit T TC bit V V bit	penetration  no resistance ranging to refusal 10-Oct-12 water level on date shown water inflow water outflow	moisture D dry M moist W wet Wp plastic limit Wl liquid limit		

Engineering Log - Hand Auger


client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 408**

Borehole ID: **HAL408**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **30 May 2016**
 date completed: **30 May 2016**
 logged by: **ODS**
 checked by: **DBC**

position: E: 368594; N: 799986 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: SL588

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
method & support: 1 penetration 2 3 HA N Not Encountered	VS >202 kPa VS >202 kPa VS 173/44 kPa VS 185/44 kPa VS 166/36 kPa VS 190/44 kPa VS >202 kPa VS UTP	Not Encountered	VS >202 kPa VS >202 kPa VS 173/44 kPa VS 185/44 kPa VS 166/36 kPa VS 190/44 kPa VS >202 kPa VS UTP	RL (m) 0.5 1.0 1.5 2.0	depth (m) 0.5 1.0 1.5 2.0	graphic log 	classification symbol SOIL TYPE: plasticity or particle characteristic, colour, secondary and minor components	ORGANIC SILT: low plasticity, dark brown.	D to M	VSt to H	50 100 150 200	2 4 6 8 10	TOPSOIL
								SILT: non plastic to low plasticity, orange brown, with trace fine grained sand.	M			VOLCANIC ASHES	
								SILT: low plasticity, brown to orange brown, with trace clay and with trace fine to coarse grained sand. Greasy.				MATUA SUB-GROUP	
								1.0 m: becoming orange brown					
								1.2 m: with minor clay					
	1.75 m: with minor to some fine to coarse grained sand												
	Sandy SILT: non plastic, orange brown, greasy.												
	Hand Auger HAL408 terminated at 2.0 m Target depth												

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:41

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud C casing N nil	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear, peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
penetration  no resistance ranging to refusal	water 10-Oct-12 water level on date shown water inflow water outflow	moisture D dry M moist W wet Wp plastic limit Wl liquid limit		

* bit shown by suffix
 e.g. AD/T
 B blank bit
 T TC bit
 V V bit

Engineering Log - Hand Auger



Borehole ID: **HAL411**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **30 May 2016**
 date completed: **30 May 2016**
 logged by: **ODS**
 checked by: **DBC**

client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 411**

position: E: 368547; N: 799989 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: SL588

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
	1 2 3							SOIL TYPE: plasticity or particle characteristic, colour, secondary and minor components			remoulded peak		
			VS >202 kPa					ORGANIC SILT: low plasticity, dark brown.	M	VSt to H			TOPSOIL
			VS >202 kPa		0.5			SILT: non plastic to low plasticity, orange brown, with trace fine grained sand and with trace clay. Greasy.					VOLCANIC ASHES
			VS >202 kPa										
			VS 172 kPa		1.0			1.0 m: with trace fine to coarse grained sand					
			VS 190 kPa										
			VS >202 kPa		1.5								
			VS >202 kPa										
			VS >202 kPa		2.0								
			VS >202 kPa					Hand Auger HAL411 terminated at 2.0 m Target depth					

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:41

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing penetration  water 	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	--	--	--	--







* bit shown by suffix
 e.g. AD/T
 B blank bit
 T TC bit
 V V bit



Engineering Log - Hand Auger

client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 412**

Borehole ID: **HAL412A**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **30 May 2016**
 date completed: **30 May 2016**
 logged by: **NM**
 checked by: **DBC**

position: E: 368531; N: 799985 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: DR2244

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
HA N Not Encountered	1 2 3	VS > 183 kPa VS 55/ 19 kPa VS > 183 kPa VS > 183 kPa VS > 183 kPa VS 151/ 43 kPa VS > 183 kPa					VS	SILT: low plasticity, orange brown, with minor clay, trace fine to medium grained sand..	D	VSt			VOLCANIC ASHES
							ML	SILT: low plasticity, orange brown, with some clay, trace fine grained sand, greasy.	M	St			MATUA SUB-GROUP
								0.7 m: becoming yellow brown with trace fine to medium grained sand.		VSt to H			
							SP	SAND: fine to medium grained, yellow, with minor silt.	D	L to MD			
							ML	SILT: low plasticity, pale grey yellow, with some fine to medium grained sand.	M to W	VSt to H			
Hand Auger HAL412A terminated at 2.0 m Target depth													

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing penetration  no resistance ranging to refusal water  10-Oct-12 water level on date shown water inflow water outflow	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoued (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System moisture D dry M moist W wet Wp plastic limit Wl liquid limit	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
---	---	--	--	--

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:41

Engineering Log - Hand Auger



client: **THE LAKES**
 principal:
 project: **THE LAKES STAGE 3E GCR**
 location: **CENTRE OF LOT 412**

Borehole ID: **HAL412B**
 sheet: 1 of 1
 project no: **GENZTAUC13086AP**
 date started: **09 Jun 2016**
 date completed: **09 Jun 2016**
 logged by: **ODS**
 checked by: **DBC**

position: E: 368527; N: 799982 (Datum Not Specified) surface elevation: Not Specified angle from horizontal: 90° DCP id.:
 drill model: drilling fluid: hole diameter : 50 mm vane id.: SL588

drilling information				material substance									
method & support	penetration	water	samples & field tests	RL (m)	depth (m)	graphic log	classification symbol	material description	moisture condition	consistency / relative density	vane shear (kPa)	DCP (blows/100 mm)	structure and additional observations
	1 2 3							SOIL TYPE: plasticity or particle characteristic, colour, secondary and minor components			remoulded peak		
HA			VS 156/ 44 kPa		0.5			SILT: non plastic to low plasticity, orange brown, with trace fine to medium grained sand. Greasy.	M	VSt to H	⊕ ⊙		MATUA SUB-GROUP
			VS >202 kPa					0.5 m: with trace clay			⊕ ⊙		
		Not Encountered	VS >202 kPa		1.0						⊕ ⊙		
			VS 156/ 29 kPa								⊕ ⊙		
			VS 118/ 38 kPa		1.5			1.5 m: becoming grey-brown and non-plastic, with some fine to coarse grained sand			⊕ ⊙		
			VS 122/ 69 kPa								⊕ ⊙		
					2.0			Hand Auger HAL412B terminated at 2.0 m Target depth					

CDF_0_9_06_LIBRARY.GLB rev:AN Log COF BOREHOLE: NON CORED + DCP STAGE 3E HAS:GPJ <<DrawingFile>> 21/06/2016 11:41

method AD auger drilling* AS auger screwing* HA hand auger W washbore HA hand auger	support M mud N nil C casing	samples & field tests B bulk disturbed sample D disturbed sample E environmental sample SS split spoon sample U## undisturbed sample ##mm diameter HP hand penetrometer (kPa) N standard penetration test (SPT) N* SPT - sample recovered Nc SPT with solid cone VS vane shear; peak/remoulded (kPa) R refusal HB hammer bouncing	classification symbol & soil description based on Unified Classification System	consistency / relative density VS very soft S soft F firm St stiff VSt very stiff H hard Fb friable VL very loose L loose MD medium dense D dense VD very dense
* bit shown by suffix e.g. AD/T B blank bit T TC bit V V bit	penetration  water 	moisture D dry M moist W wet Wp plastic limit Wl liquid limit		